

DT04 Rec'd PCT/PTO 2 4 SEP 2004

AMENDMENTS TO THE CLAIMS

The following Listing of Claims replaces all prior listings, and versions, of claims in the subject patent application.

Listing of Claims:

On a new line before claim 1, please insert -- I Claim: --

1 (currently amended): Device for driving animals in an oblong corridor section (21) by means of a driving gate (2), which can be moved from one end of the corridor section to the other, ~~characterized in that it comprises~~ comprising a first transport arrangement (3, 5, 10, 12) to move the driving gate (2) in the corridor section in ~~the~~ a longitudinal direction of the section from a first position (2b) at one end of the section to a second position (2c) at the other end, and to move the gate (2) in the opposite direction after it has been brought outside the corridor section, from a position (2d), which is opposite the second position (2c) in the corridor section, to a position (2a) which is opposite the first position (2b) in the corridor section, which first arrangement comprises a displaceable mounting part (6), which can be moved in the longitudinal direction of the section over a distance corresponding to the distance between the first position (2b) and the second position (2c) of the gate, and ~~that it comprises~~ a second transport arrangement (13, 14, 18, 19) to pull the gate sideways out from the corridor section in the plane of the gate from the second position (2c) in the corridor section, and to push the gate sideways into the corridor section in the plane of the gate from the position (2a), which is opposite the first position (2b) in the corridor section, which second arrangement comprises a second displaceable mounting part (16), to which the gate (2) is fastened and which can be moved transversely to the longitudinal direction of the section over a distance corresponding to at least the width of the driving gate (2).

2 (currently amended): Device according to claim 1, ~~characterized in that~~ wherein the second transport arrangement is suspended in the mounting part (6) of the first transport arrangement.

3 (currently amended): Device according to claim 1, ~~characterized in that~~ wherein the first transport arrangement has at least two guiding surfaces (3), which are parallel to each

other and extend in the longitudinal direction of the section, along which guiding surfaces the first mounting part (6) can be displaced.

4 (currently amended): Device according to claim 1, ~~characterized in that~~ wherein the first arrangement comprises a motor (8) to move the displaceable part (6) in the longitudinal direction of the section.

5 (currently amended): Device according to claim 4, ~~characterized in that~~ wherein the first transport arrangement comprises an oblong element (12), which extends in the longitudinal direction of the section, and ~~that wherein~~ the motor ~~operate~~ operates a coupling device (10), the coupling surfaces of which engage with surfaces on the oblong element (12).

6 (currently amendment): Device according to claim 1, ~~characterized in that~~ wherein the second transport arrangement comprises a motor to move the displaceable part (16) with the gate (2) transversely to the longitudinal direction of the section.

7 (currently amended): Device according to claim 6, ~~characterized in that~~ wherein the second transport arrangement comprises an oblong element (19), which extends transversely to the longitudinal direction of the section and has surfaces to engage with coupling surfaces of a coupling device (18) on the second mounting part (16), and ~~that wherein~~ the driving shaft of the motor can rotate the oblong element (19).

8 (currently amended): Device according to claim 1, ~~characterized in that~~ wherein the second arrangement has at least two guiding surfaces (14), which are parallel to each other and ~~extends~~ extend transversely to the longitudinal direction of the section, along which guiding surfaces the second mounting part (16) with gate can be displaced.

9 (currently amended): Device according to claim 1, ~~characterized in that it~~ comprises further comprising a control unit which ~~is designed to co-ordinate~~ coordinates the movement of the first and second transport arrangements.

10 (currently amended): Device according to claim 9, ~~characterized in that~~ wherein the control unit is designed to co-ordinate the operation of motors in the first and second transport arrangement.

11 (currently amended): Device according to claim 1, ~~characterized in that~~ wherein the driving gate (2) is mainly plane.

12 (currently amended): Device according to claim 1, ~~characterized in that it comprises~~ including a side wall (22) on each long side of the corridor section (21).

13 (currently amended): Device according to claim 12, ~~characterized in that~~ wherein one side wall (22) has a first gap (26) through which the driving gate (2) can be pulled sideways out from the corridor section and a second gap (25) through which the gate (2) can be pushed sideways into the corridor section, and ~~that~~ wherein the second displaceable mounting part (16) can be moved over a distance correspondence to the width of the gate (2) and the thickness of the wall, together.

14 (currently amended): Device according to claim 1, ~~characterized in that it also comprises~~ further comprising a gate (24) which is placed at the second position (2c) of the driving gate (2) on the down-stream side of the position (2c) in relation to the driving direction.

15 (currently amended): Device according to claim 1, ~~characterized in that it also comprises~~ further comprising a gate (23) at the first position (2b) of the driving gate (2) on the up-stream side of the position (2b), which gate can be opened partially to a position which allows animals to walk one at a time through the passage formed by the opening process, and ~~that~~ wherein the gate (23) can also be opened completely to form an opening of the same width as the corridor section, which opening allows several animals to be driven forwards next to each other.

16 (currently amended): Device according to claim 1, ~~characterized in that it comprises~~ wherein the device includes two gates (23, 24), which are placed at the first and second positions (2b, 2c) of the driving gate (2), on either side of the section which is operated by the gate (2) when it is moved from the first to the second position.

17 (canceled).

18 (currently amended): Method for driving animals in an oblong corridor section (12) by means of a driving gate (2) which can be moved from one end of the corridor section to the other, ~~characterized in~~ including:

~~that~~ removing a blockage, if present in ~~the~~ an upstream end of the corridor section, ~~is removed,~~

~~that~~ driving animals ~~are driven~~ into the corridor section (21) through the upstream end,

~~that~~ pushing the driving gate (2) ~~is pushed~~ into the corridor section when a desired number of animals have passed into the section, from a position (2a) of the gate outside the section to a first position (2b) inside the section in its upstream end,

~~that~~ removing a blockage, if present in the downstream end of the corridor section, ~~is removed,~~

~~that~~ moving the driving gate (20) ~~is moved~~ to a second position (2c) in the corridor section in the downstream end, driving the animals out from the corridor section,

~~that~~ re-establishing any blockage in the downstream end of the corridor section ~~is re-established~~ in front of the driving gate (2),

~~that~~ moving the driving gate (2) ~~is moved~~ sideways to a position (2d) outside the corridor section, and

~~that~~ returning the driving gate (2) ~~is returned~~ outside the corridor section to the position (2a) opposite the first position (2b) in the corridor section, ~~and~~

~~that the process steps are repeated as required.~~

19 (currently amended): Method according to claim 18, ~~characterized in that~~ wherein the corridor system comprises an entrance gate (23) and an exit gate (26) that allow blockage of the corridor section in the upstream end and downstream end, respectively and further comprising

a) ~~that~~ opening the entrance gate (23) in the upstream end of the corridor section (21) ~~is opened and that~~ and driving animals ~~are driven~~ past the gate and into the corridor section (21),

~~a- b)~~ b) that closing the entrance gate (23) ~~is closed~~ when a desired number of animals have passed,

~~b- c)~~ c) that pushing the driving gate (2) ~~is pushed~~ into the corridor section from a position (2a) outside the section to a first position (2b) inside the section, which is in front of the entrance gate (23)

~~c- d)~~ d) that opening the exit gate (24) in the downstream end of the corridor section (21) ~~is opened, and that~~ moving the driving gate (2) ~~is moved~~ to a second position (2c) in the corridor section behind the exit gate (24), thereby driving the animals out from the corridor section,

~~d- e)~~ e) that closing the exit gate (24) ~~is closed~~ in front of the driving gate (2),

~~e- f)~~ f) that moving the driving gate (2) ~~is moved~~ sideways to a position (2d) outside the corridor section, and

~~f- g)~~ g) that returning the driving gate (2) ~~is returned~~ outside the corridor section to the position (2a) opposite the first position (2b) in the corridor section, ~~and~~

g) ~~that the process steps a) to f) are repeated as required.~~

20 (new): Device according to claim 15, further comprising a control unit which coordinates the movement of the first and second transport arrangements and controls the opening of the gate (23).

21 (new): Device according to claim 16, further comprising a control unit which coordinates the movement of the first and second transport arrangements and controls the opening of the gates (23, 24).